Chartwell Railings

Manufacturer: Jacksons Fencing.
Web:www.jacksons-fencing.co.uk.
Tel:+44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose .

Product reference: Chartwell Railings

- Pales and post finish/ colour:
  [Galvanized and powder coated, black RAL 9005]. - Standard.
  [Galvanized and plasticoat coated]. - For applications near sea water.
  [Galvanized and powder coated, blue BS 20-C-40].
  [Galvanized and powder coated, blue RAL 5010].
  [Galvanized and powder coated, brown RAL 8017].
  [Galvanized and powder coated, green RAL 6005].
  [Galvanized and powder coated, grey RAL 7012].
  [Galvanized and powder coated, red RAL 3020].
  [Galvanized and powder coated, white RAL 9010].
  [Galvanized and powder coated, yellow RAL 1018].
  [Galvanized and powder coated, BS]. - Special order, insert requirements.
  [Galvanized and powder coated, RAL]. - Special order, insert requirements.

- Fixing:
  [As standard].
  [Base plates].

- Gates:
  -Type:
  [Not required].
  [Cantilever sliding].
  [Swing].

-Operation:
[Not applicable].
[Automatic]. Gate Safe compliant: EN 13241-1:2003 (EN 12453:2003 / EN 12445:2000 / EN 12978:2003 / EN 12604:2000 / EN 12605:2000)
[Manual].

- Bottom profile:
  [Horizontal].
  [Raked].
  [Stepped].

As standard
Size:

- Panel:

- Height: 1100 mm.
- Pales (diameter): 19 mm, CHS.
- Pale pitch: 100 mm.
- Post centres: 3000 mm.
- Post (diameter): 60.3 mm, CHS.

- Gate:

- Height: 1050 mm.
- Pales (diameter): 19 mm, CHS.
- Pale pitch: 100 mm.
- Post (diameter): 89.9 mm, CHS.

Rails:
95 x 65 mm, Jakcure treated timber with a natural finish.

Fixing:
Dependant on the application and the ground conditions. The standard fixing method involves posts being secured below the ground, consult manufacturer's literature for post foundation requirements.

Options

Gate:
Matching gates are available for the railings, consult manufacturers literature for more details.

Bottom profile:
Can be raked or stepped to suit ground contours.

Installation
In accordance to manufacturers instructions