

## NOTES.

ALL DIMENSIONS ARE IN mm (UNO) GAPS UNDER FENCING ARE NOMINAL DUE TO GROUND LEVELS. CAPPING & COUNTER RAILS MAYBE REMOVE IF NOT REQUIRED (PLEASE ASK SALES FOR FURTHER DETAIL)

## MATERIALS.

ACOUSTIC BOTTOM BOARD: 140 x 34 thk (120 Nom. FACE) ACOUSTIC T & G BOARD: 140 x 34 thk (123 Nom. FACE)

CAPPING RAIL: 145 x 34 thk PAR COUNTER RAIL: 70 x 34 thk PAR POST COVER BOARD: 120 x 35 thk TIMBER BATTEN: 100 x 50 thk SAWN FINISH STEEL POSTS: UNIVERSAL BEAMS ASSESSED TO SUIT SITE LOCATION. BASEPLATES: FULLY WELDED TO POSTS

ALL FIXINGS ARE GALVANISED OR STAINLESS STEEL.

FINISH.

TIMBER: JAKCURED TREATED.

STEEL: GALVANISED TO BS EN ISO 1461

**Jacksons** Stowting Common, Near Ashford, Kent. TN25 6BN Telephone: 01233 750393 Fencing

Fax: 01233 750403 www.jacksons-fencing.co.uk

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd, And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission. DO NOT SCALE - IF IN DOUBT ASK

END POST COVER STRIP

BOARDS AND NAIL BATTEN

TO BE FLUSH WITH

29/03/23 NOTES ADDED

31/03/2020 NEW BORDER + NOTES 04/01/08 HEIGHTS SEPARATED  $\langle 0 \rangle$ 11/06/07 ORIGINAL ISSUE

Drawn JR SALES DRAWING (WITH CAPPING) Date 11/06/2007 Drawing No. **CUSTOMER** Checked AT Size

4810 TYPICAL BOARD LENGTH 2400 END BOARD LENGTH 145 BOTTOM BOARD WITH NO GROOVE 100 125 TYP ALL BOARDS SUPPLIED AT 4.8m Lq LEND BOARDS CUT TO 2.4m Lq COVER BOARDS OVER GAPS BOARD JOINS ARE STAGGERED & BETWEEN ACOUSTIC BOARDS ARE CO-INCIDENT TYPICALLY FINISH WITH POST POSITIONS ~50mm ABOVE FGL VIEWED FROM OUTSIDE REFER TO SHEET 9 FOR LEAVE SPOIL SO THAT BASE BOARD CONTACTS THE GROUND TO AVOID AIR GAP MORE BASEPLATE DETAILS

2350 TYPICAL

END POST CENTRES

JAKOUSTIC HIGHWAY FENCE - BASEPLATED (WITH CAPPING) - 4m HIGH

JAKOUSTIC HIGHWAY FENCE - BASEPLATED 4m HIGH J7/01296 1:35 Scale ACK No. Sheet 5 U.0.S

2410 TYPICAL

INTERMEDIATE POST CENTRES

COVER STRIP TO BE ACCURATELY

CENTRED WITH NAIL BATTEN

**INSIDE** 

ALL INTER POSTS -