

# **Heavy Metal Field Gates**

Manufacturer: Jacksons Fencing. Web: <a href="https://www.jacksons-fencing.co.uk">www.jacksons-fencing.co.uk</a>.

Tel:+44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose.

Product reference: Heavy Metal Field Gates.

#### •Size:

[As drawing ???].

#### •Type:

[440800]. - Heavy gates, 1200 mm long. [441100]. - Heavy gates, 2100 mm long. [441200]. - Heavy gates, 2400 mm long. [441300]. - Heavy gates, 2700 mm long. [440200]. - Heavy gates, 3000 mm long. [440400]. - Heavy gates, 3600 mm long. [440500]. - Heavy gates, 4200 mm long. [440600]. - Heavy gates, 4600 mm long.

# •Post:

(AND)

[453200] – Dia 89 x 1875mm long hanging post for heavy field gates (for gates up to 3.3m) [453100]. – Dia 114 x 1875mm long hanging post for heavy field gates (for gates 3.6m and above) [453600]. – 1900 mm long slam post for heavy field gates.

#### Accessories:

[None].

[453880]. - Drop bolt.

[453700]. - Loop over catch for pairs of gates.

#### As standard

# Height:

1150 mm.

## **Posts:**

- Hanging posts: 1875 mm long, 114mm diameter CHS
- Slamming post: 1900 mm long, 87mm diameter CHS.

### Hang and Slam stile:

50 x 25 mm RHS.

# **Top and Bottom Rail:**

41.5 mm diameter CHS.

#### Middle Rails:

32 mm Diameter CHS.



# Jacksons Fencing NBS Specification

Manufactured from high quality materials for long lasting use.

#### **Features:**

- Hot Dip Galvanized finish as standard to BS EN 1461 and can also be powder coated to BS EN 13438 in nine standard colours at extra cost and any other RAL colour.
- Low Life time cost.
- Padlockable sliding latch.
- Adjustable bottom hinge.
- Box section hang and slam stiles.
- Six bar gate with extra strong tubular rails.

#### Installation

In accordance to manufacturers instructions