

# BARBICAN® SLIDING GATES



Barbican® sliding gates are a perfect match to Barbican® fencing and share all the principle design features of our fully welded pale-through-rail construction.

- Ideal for applications where space is limited or ground obstacles need to be spanned
- Available in a range of standard widths to span up to 20m for cantilever and 28m for tracked gates. Contact us for special requirements
- Heights of up to 3m
- Vertical pales 25mm x 25mm RHS
- Single or double leaf options available
- Cantilever or tracked options available
- Manual or automated operation
- Effective operation in applications subject to high wind loading

## FINISHES

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

## STANDARD COLOURS

- Green RAL 6005, Black RAL 9005, Blue RAL 5010, Red RAL 3020, Yellow RAL 1018, White RAL 9010, Grey RAL 7012, Brown RAL 8017, Blue BS20-C-40
- Architectural grade powder coating
- Other colours on request

## FINIALS





- Materials:  
Portals: 80 x 80mm  
Stiles: 60 x 60mm  
Rails: 60 x 40mm  
Running tube for cantilever gate: 178mm outer diameter  
Running tube for tracked gate: 200 x 100mm
- Automated:  
Class 1 - hold open/close  
Class 3 - UKCA marked including flashing light, photocells, and safety edges

## OPTIONS

- Manual
- Automated

## AUTOMATION

- Ask our team about automating your gate. All of our gate automation engineers are DHF qualified to a minimum of level 2.