

SLIDING GATES



Sliding Gates

Sliding gates are ideal for applications where there is insufficient room for swing gates to open into and where higher security is required. Even where the ground is not level, the cantilever sliding gates run smoothly on nylon wheels, making them surprisingly quiet.

An alternative to cantilever sliding gates is tracked sliding gates, the advantage is that they can span larger opening widths and have a lower profile from the ground, with the gate running along a track set in level ground.

Gate Automation Safety

Jacksons automated gates and barriers meet with the essential health and safety requirements and are CE marked as required by law. Additionally the products are designed and engineered to exceed the standards set out in BS EN 12978 and BS EN 12453 in relation to gate safety.

GATE OPTIONS

- Manual
- Automated
- Tracked
- Cantilever
- Telescopic
- Choice of infill

PORTAL OPTIONS

- Overlength set in concrete as standard - optional
- Baseplated to bolt down onto concrete - as standard



Single Leaf Gate (cantilever)

HEIGHT (MM)	OPENING (MM)	INFILL OPTIONS
1800 / 2000 / 2500 / 3000	Up to 12,000	Vertical Bar / Welded Mesh / Tubular / Bow Top / Acoustic

Double Leaf Gate (cantilever)

HEIGHT (MM)	OPENING (MM)	INFILL OPTIONS
1800 / 2000 / 2500 / 3000	Up to 24,000	Vertical Bar / Welded Mesh / Tubular / Bow Top / Acoustic

FINISHES

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

STANDARD COLOURS

- Black RAL 9005
- Green RAL 6005
- Other colours are available on request