

## BARBICAN® SWING GATES



Galvanised Double Leaf Swing Gate – Manual



Black Single Leaf Swing Gate – Manual

Barbican® swing gates are a perfect match to Barbican® fencing and share all the principle design features of our fully welded pale-through-rail construction.

### Features

- Available in a range of standard widths up to 12m and heights to 3m for pedestrian and vehicular access
- Pales 25mm x 25mm RHS
- Horizontal rails for all gates are 60 x 40mm
- Single or double leaf options available
- Manual or automated operation
- Complete with tamper-proof hinges that allow the gate to swing through an angle of 180 degrees (manual only)
- Square hollow section gate posts made in three sizes; 100mm, 120mm and 150mm depending on the gate height and width
- Gates over 3.5m long feature additional diagonal bracing struts

### POST OPTIONS

- Over length set in concrete as standard
- Base plated to bolt down onto concrete

### FINISHES

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

### STANDARD COLOURS

- Green RAL 6005, Black RAL 9005, Blue RAL 5010, Red RAL 3020, Yellow RAL 1018, White RAL 9010, Grey RAL 7012, Brown RAL 8017, Blue BS20-C-40
- Architectural grade powder coating
- Other colours on request



## Locking Options

- Slide latch (as standard)
- Key lock
- Mechanical coded lock
- Push pad latch
- Electric strike lock
- Magnetic latch

## OPTIONS

- Manual
- Automated

## AUTOMATION

- Ask our team about automating your gate. All of our gate automation engineers are DHF qualified to a minimum of level 2.

## FINIALS

