

SENTRY® SLIDING GATES

Sentry sliding gates are a perfect match to Sentry fencing and shares all the principle design features of our welded semi pale-through-rail construction.

- Ideal for applications where space is limited or ground obstacles need to be spanned
- Pales Ø 32mm
- Rails 60 x 40mm
- Single or double leaf options available
- Cantilever or tracked options available
- Manual or automated operation
- Effective operation in applications subject to high wind loading
- Available in a range of standard widths to span up to 30m and in heights of 3m
- Gateposts are square hollow section, made in three sizes; 100mm, 120mm and 150mm depending on the height and width of gate
- 30mm high, sharp pointed steel security comb on gates over 1.5m high, unless specified

FINISHES

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

PORTALS

- Base plated to bolt down onto concrete



- Materials: Portals: 80 x 80 Sq, Stiles: 60 x 60 Sq, cantilever running tube: ø178, Tracked running tube: 200 x 100
- Automated: Class 1 hold to open / close or Full Class 3 operation to suit current CE safety regulations including flashing light, photocells & safety edges. Motors to suit various gate sizes and open/close cycles.

CONTACT

T: 0800 41 43 43

E: security@jacksons-fencing.co.uk

W: www.jacksons-security.co.uk