



ADJUSTABLE GATE HINGES ALLOW EASY OPERATION OF THE BARRIER WHICH CAN BE LOCKED OPEN IN EITHER 90° OR 135° POSITIONS  
 SECURITY FIXINGS ARE USED EXTENSIVELY THROUGHOUT THE ASSEMBLY.

BOTH THE LOCKING BOLT AND THE HANDLE CAN BE PADLOCKED TO THE SLAM POST WHEN THE BARRIER IS CLOSED AND LOCKED.  
 THE SECURITY PLATE PREVENTS THE BARRIER FROM BEING FORCED OFF THE LOCKING BOLT.  
 THE HANDLE IS USED TO GUIDE THE BARRIER WHEN IT IS BEING MOVED TO EITHER OF THE OPEN POSITIONS - 90° OR 135°.

VIEWED FROM OUTSIDE  
 BARRIER OPENS AWAY FROM VIEWER  
 LEFT HAND HANG OPEN IN

FINISH: GALVANISED TO BS EN 1461:1999 & POLYESTER POWDER COATED IF REQUIRED

**Jacksons**  
**FINE FENCING**

Stowting Common  
 Near Ashford,  
 KENT. TN25 6BN  
 Telephone : 01233 750393  
 Fax: 01233 750403  
 Int. Tel : +44 (0)1233 750393

DO NOT SCALE - IF IN DOUBT ASK

- ③ 08/11/2018 OPENING NOTE
- ② 26/06/2018 PPC NOTE IF REQ'D
- ① 17/02/10 BASE SIZES UPDATED
- ① 30/10/2003 Original Issue

Drawn JWG	
Date	30/10/2003
Checked Chris J	
Size	Scale 1:30 U.O.S
A3	

TITLE STD LAYOUT OF MAX HEIGHT Br. 2.3 m HIGH x 7.0m w LHH OPEN IN	
CUSTOMER SALES INFORMATION	Drawing No. 03 J7/04159
ACK No.	Sheet 1 of 2

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd.  
 And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.