



OPTIONAL MITRE CORNER
 ENSURE SUPPORTING BRACKETS ARE WITHIN 1.5m OF CORNER TO PROVIDE ADEQUATE SUPPORT

NOTES.
 ALL DIMENSIONS ARE IN mm (UNO) FINISH.
 GALVANISED TO BS EN ISO 1461
 POWDER COATED: IF REQUESTED

| CUSTOMERS REQUIREMENTS | | | |
|-----------------------------|-----|-----------------------------------|-----------------------------|
| DESCRIPTION | QTY | BASE FIXINGS PER BRACKET REQUIRED | TOTAL BASE FIXINGS REQUIRED |
| END BRACKET | | (3) | |
| INTERMEDIATE BRACKET | | (2) | |
| JOINING TUBE | | | |
| CORNER MITRE SUPPORT | | | |
| ROTA COBRA SPIKE | | | |
| ø41.5 TOP RAIL TUBE x 6m Lg | | | |

Jacksons Fencing

Stowting Common, Near Ashford, Kent. TN25 6BN
 Telephone: 01233 750393
 Fax: 01233 750403
 www.jacksons-fencing.co.uk
 www.jacksons-security.co.uk

DO NOT SCALE - IF IN DOUBT ASK

1 17/03/2020 NEW BORDER + NOTES
 0 21/09/11 Original Issue

Drawn J.REED
 Date 26/07/2011
 Checked
 Size A3 Scale 1:5 U.O.S

TITLE SALES DRAWING
 ROTARY COBRA SPIKE - WALL TOP MOUNTED
 CUSTOMER
 Drawing No. J4/04154
 Sheet 1
 ACK No.

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd, And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.