



NOTES.
 ALL DIMENSIONS ARE IN mm (UNO) FINISH.
 GALVANISED TO BS EN ISO 1461
 POWDER COATED: IF REQUESTED

OPTIONAL MITRE CORNER

ENSURE SUPPORTING BRACKETS ARE WITHIN 1.5m OF CORNER TO PROVIDE ADEQUATE SUPPORT

| CUSTOMERS REQUIREMENTS | | | |
|--|-----|------------------------------|------------------------|
| DESCRIPTION | QTY | FIXINGS PER BRACKET REQUIRED | TOTAL FIXINGS REQUIRED |
| END BRACKET | | (3) | |
| INTERMEDIATE BRACKET | | (2) | |
| CORNER BRACKET c/w M10 x 30 Lg RESISTROX SCREW | | (2) | |
| SWIVEL BRACKET | | | |
| JOINING TUBE | | | |
| CORNER MITRE SUPPORT | | | |
| SINGLE ROTA SPIKE | | | |
| Ø41.5 TOP RAIL TUBE x 6m Lg | | | |

Jacksons Fencing

Stowting Common, Near Ashford, Kent. TN25 6BN
 Telephone: 01233 750393
 Fax: 01233 750403
 www.jacksons-fencing.co.uk
 www.jacksons-security.co.uk

DO NOT SCALE - IF IN DOUBT ASK

- ③ 13/03/2020 NEW BORDER + NOTES
- ② 28/03/19 Top Rail Updated
- ① 02/12/15 Rota spikes updated
- ① 12/06/06 Original Issue

Drawn SL
 Date 12/06/2006
 Checked CJ
 Size A3
 Scale 1:5 U.O.S

TITLE SALES DRAWING
 ROTASPIKE ABOVE PALISADE FENCING
 CUSTOMER
 ACK No.
 Drawing No. J4/04007
 Sheet 3

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd, And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.