

Manufacturer: Jacksons Fencing

Web: www.jacksons-security.co.uk

Tel: +44 (0)1233 750393 | 0800 953 3699

Product Reference: Ball Stop

Service Life of Fencing

Metal fencing and gates designed and manufactured to be fit for purpose and providing a minimum 25 year guarantee, delivering the lowest whole life cost and significantly reduced carbon footprint.

Fencing & Posts:

4000mm High, Post: 4150m Long, 60.3mm Ø circular hollow section, 3000mm Post Centres

5000mm High, Post: 5150m Long, 60.3mm Ø circular hollow section, 3000mm Post Centres

6000mm High, Post: 6150m Long, 60.3mm Ø circular hollow section, 3000mm Post Centres

7000mm High, Post: 7150m Long, 60.3mm Ø circular hollow section, 3000mm Post Centres

8000mm High, Post: 8150m Long, 60.3mm Ø circular hollow section, 3000mm Post Centres

9000mm High, Post: 9150m Long, 60.3mm Ø circular hollow section, 3000mm Post Centres

** Delete above as required*

Post Construction:

Posts are made using circular hollow section steel hot dip galvanised inside and out to BS EN 1461 as standard

Post size will be dependent on location and fence height.

Top Rail as standard

Base plated to bolt down onto concrete 150mm below ground level

Finish / Colour:

Hot dip galvanised inside and out to BS EN ISO 1461 as standard

Hot dip galvanised inside and out to BS EN ISO 1461 then polyester powder coated with Akzo Nobel Interpon coating in standard [Black RAL 9005] [Green RAL 6005].

Fence panels and posts galvanised as standard then polyester powder coated with Akzo Nobel Interpon coating in special [Insert RAL/BS].

Marine coating required as installation is within 500m of salt water or estuary.

** Delete above as required*

Netting/Mesh:

Netting is constructed from 1.8mm black polyethylene knotless, mesh 28 x 28mm

Welded Mesh - [Galvanised / Black / Green PVC Coated]

Chain Link - [Galvanised / Black / Green PVC Coated]

NOTES:

For more information please contact Jacksons Fencing. We reserve the right to alter specification within this document at any time.