



GATES SECURED USING DROPBOLTS & PADLOCKABLE SLIDE LATCH
(PADLOCK NOT SUPPLIED)
OPTIONAL KEY LOCK AVAILABLE

DOUBLE GATE SIZES				
BETWEEN POSTS	NOM. WIDTH	CLEAR OPENING	HANG POST	MINIMUM FOUNDATION
1921	2.0m	1461	100 x 100 SHS	250 x 250 800 DEEP
2439	2.5m	1979		
2957	3.0m	2497		
3475		3015	120 x 120 SHS	300 x 300 800 DEEP
3993	4.0m	3533		
4511		4051		
5029	5.0m	4569	150 x 150 SHS	
5547		5087		
6065	6.0m	5605		
6583		6123		
7101	7.0m	6641		

NOTES.
ALL DIMENSIONS ARE IN mm (UNO)
GAPS UNDER GATES ARE NOMINAL DUE TO GROUND LEVELS.

MATERIALS.
HANG POSTS: TYPICALLY AS TABLE (ALSO ASSESSED TO SUIT SITE LOCATION)
GATE RAILS: 60 x 40 RHS
SLAM STILE: 60 x 40 RHS
HANG STILE: 60 x 60 SHS
PALES: Ø19 CHS

FINISH.
GALVANISED TO BS EN ISO 1461
POWDER COATED: IF REQUESTED

Jacksons Fencing

Stowting Common, Near Ashford, Kent. TN25 6BN
Telephone: 01233 750393
Fax: 01233 750403
www.jacksons-fencing.co.uk
www.jacksons-security.co.uk

DO NOT SCALE – IF IN DOUBT ASK

Drawn WB
Date 25/02/2020
Checked
Size A3
Scale 1:25 U.O.S

TITLE SALES DRAWING FOR TRIGUARD DOUBLE GATES
CUSTOMER
ACK No.
Drawing No. J6/04025
Sheet 2

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd, And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.

25/02/2020 ORIGINAL ISSUE