



GATES SECURED USING PADLOCKABLE SLIDE LATCH  
(PADLOCK NOT SUPPLIED)  
OPTIONAL KEY LOCK AVAILABLE

SINGLE GATE SIZES				
BETWEEN POSTS	NOM. WIDTH	CLEAR OPENING	HANG POST	MINIMUM FOUNDATION
973	1.0m	753	100 x 100 SHS	250 x 250 800 DEEP
1232		1012		
1491	1.5m	1279		
1750		1530	120 x 120 SHS	300 x 300 800 DEEP
2009	2.0m	1789		
2268		2048		
2527	2.5m	2307		
2786		2566	150 x 150 SHS	
3045	3.0m	2825		
3304		3084		
3563	3.5m	3343		

**NOTES.**  
ALL DIMENSIONS ARE IN mm (UNO)  
GAPS UNDER GATES ARE NOMINAL DUE TO GROUND LEVELS.

**MATERIALS.**  
HANG POSTS: TYPICALLY AS TABLE  
(ALSO ASSESSED TO SUIT SITE LOCATION)  
SLAM POST: 100 x 100 SHS  
GATE RAILS: 60 x 40 RHS  
SLAM STILE: 60 x 40 RHS  
HANG STILE: 60 x 60 SHS  
PALES: Ø19 CHS

**FINISH.**  
GALVANISED TO BS EN ISO 1461  
POWDER COATED: IF REQUESTED



Stowting Common, Near Ashford,  
Kent. TN25 6BN  
Telephone: 01233 750393  
Fax: 01233 750403  
www.jacksons-fencing.co.uk  
www.jacksons-security.co.uk

DO NOT SCALE – IF IN DOUBT ASK

- ③ 25/02/2020 NEW BORDER + SL & DL SPLIT
- ② 21/03/05 DROPBOLT REMOVED
- ① 05/09/00 PALE PITCH REVISED
- ① 13/04/99 ORIGINAL ISSUE

Drawn Y HALL	TITLE	SALES DRAWING FOR TRIGUARD SINGLE GATES	
Date 13/04/1999	CUSTOMER	Drawing No. J6/04025	
Checked	ACK No.	Sheet 1	
Size A3	Scale 1:20 U.O.S		

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd, And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.