## **TRI-GUARD® SWING GATES**





Tri-Guard® gates are stylish and secure with distinctive triple-cluster pales, curved tops, and decorative steel discs. Combining anti-climb and anti-scale features, Tri-Guard® offers robust performance and aesthetics. Made from galvanised tubular steel, these gates are lightweight and decorative, yet strong and secure. They perfectly complement our Tri-Guard® fencing system.

#### **Features**

- Available in a range of standard widths up to 10m and heights to 3m for pedestrian and vehicular access
- Pales Ø 19mm
- Horizontal rails for all gates are 60 x 40mm
- Single or double leaf options available
- Manual or automated operation
- Complete with tamper-proof that allow the gate to swing through an angle of 180 degrees (manual only)
- Square hollow section gate posts made in three sizes; 100mm, 120mm and 150mm depending on height and width of gate
- Gates over 3.5m long feature additional diagonal bracing struts

#### **POST OPTIONS**

- Over length set in concrete as standard
- Base plated to bolt down onto concrete

#### **FINISHES**

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

#### STANDARD COLOURS

- Green RAL 6005, Black RAL 9005, Blue RAL 5010, Red RAL 3020, Yellow RAL 1018, White RAL 9010, Grey RAL 7012, Brown RAL 8017, Blue BS20-C-40
- Architectural grade powder coating
- Other colours on request

# Jacksons Fencing







### **Locking Options**

- Slide latch (as standard)
- Key lock
- Mechanical coded lock
- Push pad latch
- Electric strike lock
- Magnetic latch

## **OPTIONS**

- Manual
- Automated

## **AUTOMATION**

 Ask our team about automating your gate. All of our gate automation engineers are DHF qualified to a minimum of level 2.