



NOTES.

ALL DIMENSIONS ARE IN mm (UNO)
GAPS UNDERNEATH GATES & FENCING ARE NOMINAL DUE TO GROUND LEVELS.
PANELS CAN BE REDUCED IN WIDTH TO SUIT THE SITE.
TIMBER SECTIONS OF PANELS TO BE ASSEMBLED ON SITE.
POSTS TO BE INSTALLED 20mm ABOVE TOP OF PANEL.
ONCE STEEL FENCE IS FULLY INSTALLED, SLATS TO BE INSERTED BETWEEN WIRES.
TOP & BOTTOM CAPPING STRIPES TO BE INSTALLED USING WOODSCREWS @ 500mm MINIMUM CENTRES.
POST COVER STRIPS FITTED USING 4 No. CSK TEK SCREWS.
REFER TO JFW15.pdf FOR INSTALLATION DETAILS

FINISH.

STEEL: GALVANISED TO BS EN ISO 1461
POWDER COATED: IF REQUIRED
TIMBER: JAKCURED

Jacksons Fencing

Stowting Common, Near Ashford,
Kent. TN25 6BN
Telephone: 01233 750393
Fax: 01233 750403
www.jacksons-fencing.co.uk

DO NOT SCALE – IF IN DOUBT ASK

1 19/02/2020 REDRAWN ON NEW BORDER
0 24/08/2016 Original Issue

Drawn LA
Date 24/08/2016
Checked Chris J
Size A3
Scale 1:20 U.O.S

TITLE SALES DRAWING
EUROGUARD COMBI FENCE – REDUCED HEIGHT OPTION
CUSTOMER
ACK No.
Drawing No. J7/01049
Sheet 4

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd, And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.