

## Decking and Balustrade

Manufacturer: Jacksons Fencing.  
Web:[www.jacksons-fencing.co.uk](http://www.jacksons-fencing.co.uk).  
Tel:+44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose .

Product reference: Decking and Balustrade.

•Decking board:

- [755600]. - Standard decking board, 3.6 m x 100 x 25 mm.
- [755900]. - Heavy decking board, 3.6 m x 150 x 32 mm.
- [755910]. - Heavy decking board, 4.8 m x 150 x 32 mm.

-Joists:

- [755100]. - Decking joist 3.0 m x 100 mm x 50 mm thickness.
- [755200]. - Decking joist 3.6 m x 100 mm x 50 mm thickness.
- [755220]. - Decking joist 3.6 m x 150 mm x 50 mm thickness.

-Supports:

- [755300]. - Decking support post 0.6 m x 100 mm diameter.
- [755400]. - Decking support post 0.9 m x 100 mm diameter.
- [755500]. - Decking support post 1.2 m x 100 mm diameter.
- [755510]. - Decking support post 1.8 m x 100 mm diameter

-Fixings:

(AND)

- [759200]. - 2 tread decking stringer (850 mm long).
- [759300]. - 3 tread decking stringer (1200 mm long).
- [759400]. - 4 tread decking stringer (1530 mm long).
- [759500]. - 5 tread decking stringer (1865 mm long)
- [Galvanized nails 75 mm].
- [Stainless steel self drilling screws 60 x 5 mm].

-Galvanized shoes:

- [756000]. - For intermediate post black powder coated, with fixing plate and bolt
- [756010]. - For end or corner post. Black powder coated, with fixing plate and bolt

•Balustrade:

- [Not required].
- [757100]. - Style 1, 1150 mm wide.
- [757200]. - Style 1, 1480 mm wide.
- [757300]. - Style 1, 1830 mm wide.
- [758100]. - Style 2, 1260 mm wide.
- [758200]. - Style 2, 1550 mm wide.
- [758300]. - Style 2, 1830 mm wide.

-Spur post:

## Jacksons Fencing NBS Specification

[Not required].

[756310]. - 100 x 100 x 1500 mm.

-Posts:

[756200]. - 1060 mm intermediate Jakpost.

[756300]. - 1060 mm corner Jakpost.

[756100]. - 1060 mm end Jakpost.

-Post for Pergola Topping:

[667400]. - 2100 mm Intermediate post.

[667440]. - 2100 mm corner post.

[668400]. - 2100 mm end post

-Balustrade gates:

[Not required].

[757900]. - Style 1 right handed.

[757990]. - Style 1 left handed.

[758900]. - Style 2 right handed.

[758990]. - Style 2 left handed.

•Accessories:

(AND)

[None].

[756350]. - Post infill piece, 25 x 50 x 2000 mm.

[756810]. - Capping rail, 2400 mm.

[756800]. - Capping rail, 3900 mm.

[755777]. - Weed Control Roll 12m roll x 1m wide

[755770]. - Weed Control Sheeting 50m roll x 1m wide

### Options

#### Post/ Capping/ Base boards:

A wide range of decking boards, posts and capping boards available, please contact manufacturer for exact details and product codes.

#### - Galvanized shoes:

Used for fixing either intermediate or end/ corner posts.

#### Balustrade:

- Style 1: Rectangular with round shape to bottom of pale complete with top and bottom rail.
- Style 2: Spindle infill complete with top and bottom rail.

#### - Spur post:

To add extra strength to balustrade, spur posts and packers can be used.

#### Balustrade gates:

1000 mm wide.

Timber decking and balustrades available with either standard or heavy duty boards.

Balustrades available in two styles, all come pre-assembled with a Jakcure finish available in three widths. Both styles slot neatly into Jakposts.

#### Features:

- Jakcured grooved boards resistant to slipping and aid drainage.
- All timber used throughout is superior quality Jakcured softwood guaranteed for twenty five years.
- Stainless steel self drilling screws 60 x 5 mm.

### Installation

In accordance to manufacturers instructions