

# Chilham Panel

# Jacksons Fencing



It's a challenge to design a solid timber fence that looks equally good on both sides. However, our Chilham panels manage just that, in a unique design, free from horizontal rails that could spoil either yours or your neighbour's view.

- All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.
- All fixings are stainless steel.
- Designed for use with slotted Jakposts®.
- Has a unique interlocking grooved board system.
- Part of our premium 'good-both-sides' range.
- Gravel boards are required where panels are in contact with the ground.

## Specification

Panel Heights: 0.91m 1.22m 1.52m 1.83m

Panel Width: 1.83m

Framing: Top/bottom - 45 x 70mm planed. Sides 45 x 51mm planed.

Panel Thickness: 51mm Infill panels: 95 x 8mm.

Assembly system with vertical pales that overlap/interlock with the infill panels.

If you need to reduce the width of a panel on site, a cut down kit is available. Always use Jakcure® End Grain Treatment on any cut timber.

## Gates

Gates are Jakcure® treated softwood, right and left hand hanging (when viewed from the outside) as standard, designed to match our Chilham Panel. Non-standard gates with custom width / heights are available as a special order and are also available as pairs (size restriction applies).

- Elegantly designed to match our Chilham Panel.
- Galvanised ring latches and adjustable 'L' hinges.
- The gate must only be used with 'L' hinges supplied.
- Wall plates are available for fitting these gates to walls.

Standard Gate Heights: 1.78m (plus capping).

Standard Gate Widths: 1m

View our website for Q40 specification documents, CAD drawings and products available to buy online.

A fully made to measure service is available. All Jacksons Fencing systems and gates may be designed and manufactured to suit site conditions.

