



NOTE: IF MORE THAN 35mm IS CUT OFF OF THE RAIL END THE INTERNAL CONNECTOR MAY NOT SLIDE FULLY BACK INTO THE RAIL

WHERE SHORT PALES ARE ADJACENT TO THE POST THE POST CAN BE INSTALLED AT FULL HEIGHT AS SHOWN

WHERE BOW PALES ARE ADJACENT TO A POST THE POST MUST BE CUT DOWN BY 90mm TO AVOID A NECK TRAP

STANDARD INSTALLATION

A MAXIMUM OF 35mm CAN BE CUT OFF OF EACH RAIL END WITHOUT CUTTING TO THE OTHER SIDE OF THE SHORT PALE

A MAXIMUM OF 35mm CAN BE CUT OFF OF EACH RAIL

VIEWED FROM OUTSIDE

NOTES.

ALL DIMENSIONS ARE IN mm (U.N.O)
GAP UNDERNEATH FENCING IS BASED UPON THE SITE BEING LEVEL.

Materials.

POSTS - $\phi 60 \times 2.25$ CHS
RAILS - $50 \times 25 \times 2$ RHS
PALES - $\phi 19 \times 1.5$ CHS

Finish.

GALVANISED TO BS EN ISO 1461:1999
POWDER COATED: IF REQUIRED

THIS PRODUCT, IF INSTALLED AS SHOWN,
CONFORMS TO BS EN 1176-1 : 1998

Drawn NM	Checked			NTS U.O.S	⑤ 18/06/10	New Border
Date NM	Size A3	Scale				

DO NOT SCALE - IF IN DOUBT ASK

Jacksons
FINE FENCING

Stowting Common, Near Ashford,
KENT. TN25 6BN
Telephone : 01233 750393
Fax: 01233 750403
Int. Tel : +44 (0)1233 750393

TITLE Standard Panel and Gate Details For
Anti - neck Trap Bowtop for Playgrounds

CUSTOMER

Drawing No.

04 J8/04018

ACK No.

Sheet 1 of 3

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd.
And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.