

# Sentry Gates

Vertical Bar Railings | Jacksons Security

Jacksons Fencing

Stowting Common | Ashford | TN25 6BN

www.jacksons-security.co.uk

+44 (0) 1233 750 393

JFS | MKT/SPC | 0610 | V1

**Jacksons**  
Quality that lasts  
Fencing & Access Solutions



Cantilever Sliding Gate



Security Comb Topping



Double Leaf Swing Gate



Standard Lock

## Sentry Single and Double Swing Gates

Sentry swing and sliding gates are a perfect match to Sentry fencing and shares all the principal design features of our welded semi pale-through-rail construction.

Available as single and double swing gates with manual operation or automated with underground, swing arm or safety-glide in-stile operators. Single and double sliding gates available in cantilever, tracked and telescopic designs as manually operated or with fully automated operation.

## Sentry Cantilever Sliding Gates

Sentry Cantilever Sliding Gates are ideal for applications where space may be restricted, the ground unlevel, or where a substantial single gate would provide higher levels of security.

The gates are smooth and virtually silent in operation and supported on a special carriage so that a single leaf is able to span widths of up to 15m over track, road, rail or even water.

Gate panels are constructed to the same exacting standards as Sentry fencing and are mounted on a substantial bottom rail of formed steel with square section steel support posts.



Sentry Gates

## Swing Gates

- Available in a range of standard widths up to 12m and heights to 3m for pedestrian and vehicular access
- Single gates are supplied as right hand hanging, opening inwards (unless specified) and are complete with key lock, handles and gate stop
- Double gates are supplied complete with key in lock, handles, centre gate stop and drop bolts
- 180° opening, adjustable, tamper-proof hinges
- 2 or 3 rail design subject to leaf width
- Gates over 3.5m long feature additional diagonal bracing struts
- 60mm x 40mm rails
- 60mm x 60mm stiles with 2mm wall thickness
- 32mm diameter CHS paling
- Square section posts at 100mm, 120mm and 150mm subject to size of gate
- Gate posts supplied to allow 800mm in ground or with base plates for bolting onto concrete
- Pale spacing conforms to Building Regulations for anti-trap
- 30mm high, sharp pointed steel security comb as a no cost option on gates over 1.5m high
- Can be extended in height to carry barbed wire, Rota-Spike or other high security extras
- Suitable for automated operation

## Finishes

- Galvanized to BS EN 1461 as standard
- Galvanized and powder coated to BS EN 13438 in one of our standard colours at extra cost
- Powder coated to any other BS and RAL colour to special order

## Cantilever Sliding Gates

- Ideal for applications where space is limited or ground obstacles need to be spanned
- Effective operation in applications subject to high wind loading
- Available in a range of standard widths to span up to 30m and in heights to 3m
- Gates to span greater widths available to special order
- Substantial construction ensures safe, reliable operation
- Supplied complete with key in lock and handles
- Heavy duty carriage for smooth, quiet operation
- 2 rail plus substantial formed steel bottom rail design
- 60mm x 40mm rails
- 120mm x 80mm portals
- 32mm diameter CHS paling
- Portals supplied with base plates for bolting onto concrete
- Pale spacing conforms to Building Regulations for anti-trap
- Automated operation ready

## Tracked Sliding Gates

We are able to supply any Sentry Gate design for tracked sliding operating on level ground if required for exceptionally heavy designs or where a single gate leaf exceeds 12m.

