

## Barbican Imperial Residential

Manufacturer: Jacksons Fencing.  
Web: [www.jacksons-fencing.co.uk](http://www.jacksons-fencing.co.uk).  
Tel: +44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose .

Product reference: Barbican Imperial Residential

- Height:  
[1 m].  
[1.25 m].

- Finish/ colour:  
[Galvanized]. - Standard.  
[Galvanized and plasticoat coated ]. - For applications near sea water.  
[Galvanized and powder coated, black RAL 9005].  
[Galvanized and powder coated, blue BS 20-C-40].  
[Galvanized and powder coated, blue RAL 5010].  
[Galvanized and powder coated, brown RAL 8017].  
[Galvanized and powder coated, green RAL 6005].  
[Galvanized and powder coated, grey RAL 7012].  
[Galvanized and powder coated, red RAL 3020].  
[Galvanized and powder coated, white RAL 9010].  
[Galvanized and powder coated, yellow RAL 1018].  
[Galvanized and powder coated, BS]. - Special order, insert requirements.  
[Galvanized and powder coated, RAL]. - Special order, insert requirements.

- Fixing:  
[As standard].  
[Base plates].  
[Wall bolts].
- Gate:  
-Type:  
[Not required].  
[Cantilever sliding].  
[Swing].  
[Tracked].  
  
-Operation:  
[Not required].  
[Automatic]. Gate Safe compliant: EN 13241-1:2003 (EN 12453:2003 / EN 12445:2000 / EN 12978:2003 / EN 12604:2000 / EN 12605:2000)  
  
[Manual].

## Jacksons Fencing NBS Specification

- Pale tops:  
[Flat]. - Standard.  
[Pointed].

- Finials:

[Not required].

[ \_\_\_\_\_ ] - Insert requirement, a range of options are available for the top of the pales and posts, consult manufacturer for exact details and product codes.

### **As standard**

#### **Size:**

- Pale pitch: 119 mm.
- Pales (diameter): 19 mm, CHS.
- Posts: 60 x 60 mm, RHS.
- Post centres (maximum): 3000 mm.
- Rails: 50 x 25 mm, RHS.
- 

#### **Fixing:**

Dependant on the application and the ground conditions. The standard fixing method involves posts being secured below the ground, consult manufacturer's literature for post foundation requirements.

### **Options**

#### **Gate:**

Matching gates are available for the railings, consult manufacturers literature for more details.

#### **Pale tops:**

Can be pointed if the overall fence height is 1500 mm above ground level, otherwise they must be flat topped.

### **Installation**

In accordance to manufacturers instructions