

# BARBICAN IMPERIAL® SLIDING GATES



Barbican Imperial® sliding gates are a perfect match to Barbican Imperial® fencing and shares all the principle design features of our fully welded pale-through-rail construction.

- Pales Ø 25mm for gates up to 2.0m
- Pales Ø 32mm for gates 2.0m and above
- Single or double leaf options available
- Cantilever or tracked options available
- Manual or automated operation
- Effective operation in applications subject to high wind loading

## FINISHES

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

## PORTALS

- Base plated to bolt down onto concrete

## FINIALS



A B D G H I M



- Materials: Portals: 80 x 80 Sq, Stiles: 60 x 60 Sq, cantilever running tube:  $\varnothing$ 178, Tracked running tube: 200 x 100
- Automated: Class 1 hold to open / close or Full Class 3 operation to suit current CE safety regulations including flashing light, photocells & safety edges. Motors to suit various gate sizes and open/close cycles.

HEIGHT (MM)	POST CENTRES (MM)	POST DIMENSIONS (MM)	OVERALL POST LENGTH (MM)
1000	3000	60 x 60	1600
1250	3000	60 x 60	1850
1500	3000	60 x 60	2100
1800	3000	60 x 60	2500
2000	3000	60 x 60	2800
2500	3000	80 x 60	3300
3000	2484	80 x 60	3800

## CONTACT

T: 0800 41 43 43

E: [security@jacksons-fencing.co.uk](mailto:security@jacksons-fencing.co.uk)

W: [www.jacksons-fencing.co.uk](http://www.jacksons-fencing.co.uk)