

TRI-GUARD® SWING GATES

**Jacksons
Fencing**



Tri-Guard® swing are a perfect match to Tri-Guard® fencing sharing the unique triple pale design feature and fully welded pale-through-rail construction.

- Available in a range of standard widths up to 10m and heights to 3m for pedestrian and vehicular access
- Pales Ø 19mm
- Horizontal rails for all gates are 60x40mm. Hanging and shutting stiles are rectangular hollow section 60x60mm
- Single or double leaf options available
- Manual or automated operation
- Complete with tamperproof hinges that allow the gate to swing through an angle of 180 degrees (manual only)
- Square hollow section gate posts made in three sizes; 100mm, 120mm and 150mm depending on height and width of gate
- Gates over 3.5m long feature additional diagonal bracing struts

FINISHES

- Hot dip galvanised to BS EN ISO 1461 as standard
- Hot dip galvanised and powder coated to BS EN 13438
- Marine coat for installations within 500m of salt water or an estuary

POST OPTIONS

- Overlength set in concrete as standard
- Baseplated to bolt down onto concrete



Locking options

- Slide latch (as standard)
- Key lock
- Mechanical digital lock
- Push pad latch
- Electric strike lock
- Magnetic latch

CONTACT

T: 0800 41 43 43

E: security@jacksons-fencing.co.uk

W: www.jacksons-fencing.co.uk