

BARRIERS CAN OPEN UP TO 180° IF REQ'D.

NOTE :
BARRIERS MUST BE PADLOCKED SECURELY IN THE OPEN AND CLOSED POSITIONS FOR SAFETY.

PIVOTING KEEP PLATE IN POST. (NODDING DONKEY)

PADLOCK THROUGH HOLE TO STOP LATCH BEING LIFTED.

PIN (DRILLED TO SUIT ON SITE) TO PREVENT BARRIER REMOVAL IF ADJUSTABLE HINGES ARE REMOVED.

BARRIER ARM IN SECURE POS'N

RAMP

SECTION A-A

NOTES.

ALL DIMENSIONS ARE IN mm (UNO)
HEIGHTS SHOWN ARE NOMINAL
DUE TO GROUND LEVELS.
FOUNDATIONS SHOWN ARE MINIMUM SIZES AND SHOULD BE ASSESSED TO SUIT GROUND CONDITIONS
MATERIALS.

HANG POST (<=8.0m) 100 x 100 SHS
(>8.0m) 150 x 150 SHS

SLAM/HOLD OPEN POST 80 x 60 RHS
BARRIER ARM: 60 x 60 SHS

TENSION WIRES ARE USED ON BARRIERS >8.0m

FINISH.

GALVANISED TO BS EN ISO 1461
POWDER COATED: IF REQUESTED

LEAF LENGTH (= BETWEEN POSTS +60mm)

TENSION WIRES (REQ'D 8.5m & OVER)

BETWEEN POSTS (6.5m - 9.0m)

(100/150)

(80)



OPTIONAL STOP OR NO ENTRY SIGNS AVAILABLE.

1000 BARRIER HEIGHT

1100 POST HEIGHT

800 DEEP

800 DEEP

650 SQ

300 SQ

Jacksons Fencing

Stowting Common, Near Ashford, Kent. TN25 6BN
Telephone: 01233 750393
Fax: 01233 750403
www.jacksons-fencing.co.uk
www.jacksons-security.co.uk

DO NOT SCALE - IF IN DOUBT ASK

- ② 03/04/2020 UNWANTED HATCH DELETED
- ① 10/10/18 TIDIED UP DIMS
- ① 12/03/18 Original Issue

Drawn JR
Date 12/03/18
Checked
Size A3 Scale 1:30 U.O.S

TITLE SINGLE WARDEN BARRIER LAYOUT
SET IN CONCRETE >6.0m WIDE

CUSTOMER
ACK No.

Drawing No.
J4/04011
4 OF 4

This Drawing Is The Property Of H.S. Jackson & Son (Fencing) Ltd, And May Not Be Copied Or Reproduced In Any Way Without Prior Written Permission.