

TRADITIONAL PALISADE



- Stainless steel fixtures and fittings.
- Post spacing nominal 2.4m.
- Pales must be installed clear of the ground.
- Choice of round or pointed pale tops
- Matching gates available.
- Gravel boards need to be used when panels are in contact with ground as part of the 25 year Jakcured guarantee.
- **25 Year Guarantee against rot and insect attack.**

FINISHES

- Jakcure pressure treated

PALE SPECIFICATION

- Pale heights: 1.0m to 1.8m (14 per section)
- Post heights: 1.5m to 2.4m
- Rails: 2.4m long nominal 87 x 38mm nominal section, scarfed both ends
- Corner posts: 1.5m to 2.4m (these are 0.6m longer than the fence height and are 100 x 100mm section nominal)
- Nails: 1kg of 50mm galvanised nails required for every 11m of 1 & 1.2m fence and for every 7m of 1.8 high fence

Traditional Round Top Palisade



Traditional Pointed Top Palisade



| FENCE TYPE | FENCE HEIGHT* (MM) | POST HEIGHT (MM) |
|----------------------------------|--------------------|------------------|
| TRADITIONAL PALISADE POSTS | 1000 | 1500 |
| | 1200 | 1800 |
| | 1800 | 2400 |
| TRADITIONAL PALISADE CORNER POST | 1000 | 1500 |
| | 1200 | 1800 |
| | 1800 | 2400 |
| TRADITIONAL PALES | 1000 | |
| | 1200 | |
| | 1800 | |

GATES

- Matching gates available
- Gate width: 1m
- Gate Height: 0.95m to 1.75m

CONTACT

T: 0800 41 43 43
E: security@jacksons-fencing.co.uk
W: www.jacksons-fencing.co.uk